



Hemisphere Mountable Monitor - 2.5" NHF Swivel Inlet, 2.5" NHM Rigid Outlet

High-Flow, Versatile Mountable Monitors

Categories: Buy Online, Portable Monitors

The Hemisphere™ Mountable Monitor provides high-flow water delivery in challenging firefighting environments, reaching up to 500 GPM (2000 LPM). Engineered for adaptability, this monitor features 360-degree rotation, allowing precise targeting in hard-to-reach areas. With multiple mounting options and a lightweight, portable design, the Hemisphere™ monitor is easy to deploy and maneuver, providing reliable water flow control for firefighting operations in confined or elevated spaces for both industrial and municipal departments

Key Features:

- **Flow Capacity** : Delivers up to 500 GPM (2000 LPM), ideal for a range of firefighting applications
- **360° Aiming** : Allows water to be directed precisely, enhancing flexibility in confined spaces
- **Quick-Attach Mounting System** : Securely mounts to various surfaces, with options like I-beam, hitch, and tank lip clamps for versatile use
- **Lightweight Aluminum Construction** : Easy to transport with a built-in carrying handle, ensuring quick setup and deployment

Task Force Tips

SKU: HPM111A



- **Water Pressurized Safety Pins** : Prevents accidental rotation/release during operation, adding safety and control
- **Adjustable Stream Straightener** : Built-in straightener ensures optimized stream reach and minimal turbulence
- **Flow Control** : Quarter-turn ball valve with a locking bail handle for precise flow management and to prevent unintentional discharge
- **Wide Compatibility** : Standard inlet and outlet sizes of 2.5" NH or BSP fittings, with options for Storz and other quick-connect attachments



Specifications

| | |
|-----------------------------------|-----------------------------------------|
| Weight | 22.600 lbs |
| Dimensions | 23.00 × 12.00 × 12.00 in |
| Color | Blue |
| Brand | Hemisphere™ |
| Bundle | Monitor Only |
| Monitor Type | Mountable |
| Monitor Supply Size (Imp) | 2.5" |
| Monitor Supply Size (Met) | 65 mm |
| Monitor Supply Type | NH Female |
| Monitor Supply Style | Rocker |
| Monitor Supply Swivel | Swivel |
| Monitor Horizontal Range | 360° |
| Monitor Vertical Range | 360° |
| Monitor Control | Manual |
| Monitor Supply Inlets | Single |
| Monitor Outlet Size (Imp) | 2.5" |
| Monitor Outlet Size (Met) | 65 mm |
| Monitor Outlet Type | NH Male |
| Monitor Outlet Style | Male Threads |
| Monitor Outlet Swivel | Rigid |
| Max Flow Rate (GPM) | 500 GPM |
| Max Flow Rate (LPM) | 2000 LPM |
| Bundle Stream Straightener | Integrated |
| Monitor Valve Type | Ball Valve |
| Safety Features | Pressurized Pins & Locking Valve Handle |



Documents

Technical Specifications and Drawings

- HPM111A
- HPM111A_Horizontal Finished Good Print – STEP
- HPM111A_80_Up Finished Good Print – STEP
- HPM111A FINISHED GOOD PRINT
- HPM111A Item Specification

Instructions For Installation, Safe Operation and Maintenance

- Hemisphere Portable Monitor
- Hemisphere Portable Monitor

Certifications & Approvals

- HEMISPHERE Declaration of Conformity

Service Procedures

- PARTS LIST: HEMISPHERE MONITOR