



## BlitzForce Portable Monitor - 2.5" NHF Swivel Rocker Inlet, 2.5" NHM Rigid Outlet

The Most Compact & Maneuverable Ground Monitor

**Categories:** Buy Online, Portable Monitors

The BlitzForce™ is a compact, efficient monitor designed for quick deployment and ease of use. Despite its smaller size, it delivers up to 500 GPM (2000 LPM), allowing firefighters to manage fire attacks with confidence. With versatile attack angles and strong flow control, the BlitzForce™ ensures safety and efficiency on the fireground. The built-in carrying handle and carbide-tipped legs make it simple to transport and stabilize, while the tie-down strap ensures secure unattended operation. The BlitzForce™ is ideal for departments requiring a highly maneuverable yet powerful monitor solution.

*Storage Bracket Sold Separately*

### Key Features:

- Flow Rate: Flows up to 500 GPM (2000 LPM) for quick knockdown capability
- Adjustable Attack Angles: Unassisted range of 30°-60°; assisted range of 20°-60°
- Carbide-Tipped Legs: Provides stability on various surfaces for secure positioning
- Built-In Carrying Handle: Enhances portability and easy deployment in the field

# Task Force Tips

SKU: XXL111A



- Compact Design: Fits easily in apparatus compartments or can be mounted for rapid access
- Safety Locking Pin: Secures the monitor to prevent unintentional water flow



## Specifications

<b>Weight</b>	15.000 lbs
<b>Dimensions</b>	23.00 × 12.00 × 12.00 in
<b>Color</b>	Silver
<b>Brand</b>	BlitzForce™
<b>Bundle</b>	Monitor Only
<b>Monitor Type</b>	Ground Attack
<b>Monitor Supply Size (Imp)</b>	2.5"
<b>Monitor Supply Size (Met)</b>	65 mm
<b>Monitor Supply Type</b>	NH Female
<b>Monitor Supply Style</b>	Rocker
<b>Monitor Supply Swivel</b>	Swivel
<b>Monitor Horizontal Range</b>	±20°
<b>Monitor Vertical Range</b>	20° – 60°
<b>Monitor Control</b>	Manual
<b>Monitor Supply Inlets</b>	Single
<b>Monitor Outlet Size (Imp)</b>	2.5"
<b>Monitor Outlet Size (Met)</b>	65 mm
<b>Monitor Outlet Type</b>	NH Male
<b>Monitor Outlet Style</b>	Male Threads
<b>Monitor Outlet Swivel</b>	Rigid
<b>Max Flow Rate (GPM)</b>	500 GPM
<b>Max Flow Rate (LPM)</b>	2000 LPM
<b>Bundle Stream Straightener</b>	Integrated
<b>Monitor Valve Type</b>	Ball Valve
<b>Safety Features</b>	Tie Down Strap



## Documents

### Technical Specifications and Drawings

- XXL111A Item Specification

### Instructions For Installation, Safe Operation and Maintenance

- BlitzForce Portable Monitor Manual

### Service Procedures

- Blitzforce: Parts list