



## BlitzFire Portable Monitor - 2.5" NHF Swivel Rocker Inlet, 2.5" NHM Rigid Outlet

The Best Ground Monitor Money Can Buy

**Categories:** Buy Online, Portable Monitors

The BlitzFire® is an adaptable, high-performance portable water monitor, ideal for fire crews facing limited manpower or challenging firefighting conditions. Delivering up to 500 GPM (2000 LPM) with full control over water flow and attack angles, the BlitzFire® can be used in either attended or unattended mode. Its exclusive safety shutoff valve ensures operation under the safest possible conditions, while its compatibility with various nozzles and foam systems adds versatility to its use. Whether you need to adjust your stream angle to reach high or low locations, the BlitzFire® is a reliable, efficient solution that maximizes fireground capabilities.

*Storage Bracket Sold Separately*

### Key Features:

- Flow Rate: Flows up to 500 GPM (2000 LPM) for powerful water delivery
- Safety Shutoff Valve: Automatically shuts off water in case of unintentional monitor movement
- Adjustable Attack Angles: 10°-46° for standard models; up to 86° for high elevation units
- Slide Valve Control: Provides complete control with six distinct detent positions for precise stream

# Task Force Tips

SKU: XX111A



management

- Foam Compatibility: Compatible with various foam systems for enhanced fire suppression
- Optional Oscillation: Covers a range of 20°, 30°, or 40° without manual adjustment for effective cooling and exposure protection
- Carbide-Tipped Legs: Offers enhanced stability on uneven terrain
- Compact Storage: Easily mounted or stored in apparatus compartments for rapid deployment



Specifications

|                            |                                 |
|----------------------------|---------------------------------|
| Weight                     | 24.500 lbs                      |
| Dimensions                 | 36.00 × 9.00 × 9.00 in          |
| Color                      | Blue                            |
| Brand                      | BlitzFire®                      |
| Bundle                     | Monitor Only                    |
| Monitor Type               | Ground Attack                   |
| Monitor Supply Size (Imp)  | 2.5"                            |
| Monitor Supply Size (Met)  | 65 mm                           |
| Monitor Supply Type        | NH Female                       |
| Monitor Supply Style       | Rocker                          |
| Monitor Supply Swivel      | Swivel                          |
| Monitor Horizontal Range   | ±20°                            |
| Monitor Vertical Range     | 10° – 46°                       |
| Monitor Control            | Manual                          |
| Monitor Supply Inlets      | Single                          |
| Monitor Outlet Size (Imp)  | 2.5"                            |
| Monitor Outlet Size (Met)  | 65 mm                           |
| Monitor Outlet Type        | NH Male                         |
| Monitor Outlet Style       | Male Threads                    |
| Monitor Outlet Swivel      | Rigid                           |
| Max Flow Rate (GPM)        | 500 GPM                         |
| Max Flow Rate (LPM)        | 2000 LPM                        |
| Bundle Stream Straightener | Integrated                      |
| Monitor Valve Type         | Slide Valve                     |
| Safety Features            | Safety Shutoff & Tie Down Strap |



## Documents

### Technical Specifications and Drawings

- XX111A Item Specification
- XX111A\_Legs\_Folded Finished Good Print – STEP
- XX111A\_Legs\_Unfolded Finished Good Print – STEP

### Instructions For Installation, Safe Operation and Maintenance

- Blitzfire Instruction Manual

### Service Procedures

- Blitzfire: Parts List